

Snijplaten M DIN EN 22568 HSS, HSS Co 5 geslepen (oude DIN 223)
Round Dies M DIN EN 22568 HSS, HSS Co 5 ground (formerly DIN 223)



Art. Nr. HSS	Art. Nr. HSS Co 5	Afmeting	Spoed mm	Buiten mm	Dikte snijplaat mm
<i>Art. No. HSS</i>	<i>Art. No. HSS Co5</i>	<i>Thread size</i>	<i>Pitch mm</i>	<i>Outside mm</i>	<i>Thickness mm</i>
SC237010	-	M 1	0,25	16,0	5,0
SC237012	-	M 1,2	0,25	16,0	5,0
SC237014	-	M 1,4	0,30	16,0	5,0
SC237016	-	M 1,6	0,35	16,0	5,0
SC237017	-	M 1,7	0,35	16,0	5,0
SC237018	-	M 1,8	0,35	16,0	5,0
SC237020	SD237020	M 2	0,40	16,0	5,0
SC237022	-	M 2,2	0,45	16,0	5,0
SC237023	-	M 2,3	0,40	16,0	5,0
SC237025	-	M 2,5	0,45	16,0	5,0
SC237026	-	M 2,6	0,45	16,0	5,0
SC237030	SD237030	M 3	0,50	20,0	5,0
SC237035	-	M 3,5	0,60	20,0	5,0
SC237040	SD237040	M 4	0,70	20,0	5,0
SC237045	-	M 4,5	0,75	20,0	7,0
SC237050	SD237050	M 5	0,80	20,0	7,0
SC237060	SD237060	M 6	1,00	20,0	7,0
SC237070	-	M 7	1,00	25,0	9,0
SC237080	SD237080	M 8	1,25	25,0	9,0
SC237090	-	M 9	1,25	25,0	9,0
SC237100	SD237100	M 10	1,50	30,0	11,0
SC237110	-	M 11	1,50	30,0	11,0
SC237120	SD237120	M 12	1,75	38,0	14,0
SC237140	SD237140	M 14	2,00	38,0	14,0
SC237160	SD237160	M 16	2,00	45,0	18,0
SC237180	SD237180	M 18	2,50	45,0	18,0
SC237200	SD237200	M 20	2,50	45,0	18,0
SC237220	SD237220	M 22	2,50	55,0	22,0
SC237240	SD237240	M 24	3,00	55,0	22,0
SC237270	-	M 27	3,00	65,0	25,0
SC237300	-	M 30	3,50	65,0	25,0
SC237330	-	M 33	3,50	65,0	25,0
SC237360	-	M 36	4,00	65,0	25,0
SC237390	-	M 39	4,00	75,0	30,0
SC237420	-	M 42	4,50	75,0	30,0
SC237450	-	M 45	4,50	90,0	36,0
SC237480	-	M 48	5,00	90,0	36,0
SC237520	-	M 52	5,00	90,0	36,0

Snijplaten MF DIN EN 22568 HSS, geslepen (oude DIN 223)
Round Dies MF DIN EN 22568 HSS, ground (formerly DIN 223)



Art. Nr. HSS	Afmeting	Spoed mm	Buiten mm	Dikte snijplaat mm
<i>Art. No. HSS</i>	<i>Thread size</i>	<i>Pitch mm</i>	<i>Outside mm</i>	<i>Thickness mm</i>
SF239030	MF 3	0,35	20,0	5,0
SF239040	MF 4	0,35	20,0	5,0
SF239041	MF 4	0,50	20,0	5,0
SF239050	MF 5	0,50	20,0	5,0
SF239051	MF 5	0,75	20,0	7,0
SF239061	MF 6	0,50	20,0	5,0
SF239060	MF 6	0,75	20,0	7,0
SF239070	MF 7	0,75	25,0	9,0
SF239082	MF 8	0,50	25,0	9,0
SF239080	MF 8	0,75	25,0	9,0
SF239081	MF 8	1,00	25,0	9,0
SF239090	MF 9	0,75	25,0	9,0
SF239091	MF 9	1,00	25,0	9,0
SF239102	MF 10	0,75	30,0	11,0
SF239100	MF 10	1,00	30,0	11,0
SF239101	MF 10	1,25	30,0	11,0
SF239110	MF 11	1,00	30,0	11,0
SF239111	MF 11	1,25	30,0	11,0
SF239121	MF 12	1,00	38,0	10,0
SF239122	MF 12	1,25	38,0	10,0
SF239120	MF 12	1,50	38,0	10,0
SF239131	MF 13	1,00	38,0	10,0
SF239130	MF 13	1,50	38,0	10,0
SF239142	MF 14	1,00	38,0	10,0
SF239140	MF 14	1,25	38,0	10,0
SF239141	MF 14	1,50	38,0	10,0
SF239150	MF 15	1,50	38,0	10,0
SF239161	MF 16	1,00	45,0	14,0
SF239162	MF 16	1,25	45,0	14,0
SF239160	MF 16	1,50	45,0	14,0
SF239181	MF 18	1,00	45,0	14,0
SF239183	MF 18	1,25	45,0	14,0
SF239180	MF 18	1,50	45,0	14,0
SF239182	MF 18	2,00	45,0	14,0
SF239201	MF 20	1,00	45,0	14,0
SF239203	MF 20	1,25	45,0	14,0
SF239200	MF 20	1,50	45,0	14,0
SF239202	MF 20	2,00	45,0	14,0

Snijplaten MF DIN EN 22568 HSS, geslepen (oude DIN 223)
Round Dies MF DIN EN 22568 HSS, ground (formerly DIN 223)



Art. Nr. HSS	Afmeting	Spoed mm	Buiten mm	Dikte snijplaat mm
<i>Art. No. HSS</i>	<i>Thread size</i>	<i>Pitch mm</i>	<i>Outside mm</i>	<i>Thickness mm</i>
SF239221	MF 22	1,00	55,0	16,0
SF239220	MF 22	1,50	55,0	16,0
SF239222	MF 22	2,00	55,0	16,0
SF239242	MF 24	1,00	55,0	16,0
SF239240	MF 24	1,50	55,0	16,0
SF239241	MF 24	2,00	55,0	16,0
SF239250	MF 25	1,50	55,0	16,0
SF239261	MF 26	1,50	55,0	16,0
SF239262	MF 26	2,00	55,0	16,0
SF239270	MF 27	1,50	65,0	18,0
SF239271	MF 27	2,00	65,0	18,0
SF239281	MF 28	1,50	65,0	18,0
SF239282	MF 28	2,00	65,0	18,0
SF239300	MF 30	1,00	65,0	18,0
SF239301	MF 30	1,50	65,0	18,0
SF239302	MF 30	2,00	65,0	18,0
SF239320	MF 32	1,50	65,0	18,0
SF239350	MF 35	1,50	65,0	18,0
SF239380	MF 38	1,50	75,0	20,0
SF239400	MF 40	1,50	75,0	20,0
SF239420	MF 42	1,50	75,0	20,0
SF239450	MF 45	1,50	90,0	22,0
SF239480	MF 48	1,50	90,0	22,0
SF239500	MF 50	1,50	90,0	22,0
SF239520	MF 52	1,50	90,0	22,0

ZE000001	Boor/Tap gel	s spuitbus	400 ml
	<i>Drill/Tapping gel</i>	<i>aerosol</i>	<i>400 ml</i>
ZE000002	Boor pasta	tube	250 gr
	<i>Drill paste</i>	<i>tube</i>	<i>250 gr</i>
ZE000003	Boor pasta	tube	750 gr
	<i>Drill paste</i>	<i>tube</i>	<i>750 gr</i>

Zeskant-snijmoeren M DIN 382 HSS, geslepen
Hexagonal solid square bolt die M DIN 382 HSS, ground



Art. Nr. HSS	Afmeting	Spoed mm	Sleutelwijdte mm	Dikte snijplaat mm
<i>Art. No. HSS</i>	<i>Thread size</i>	<i>Pitch mm</i>	<i>Outside mm</i>	<i>Thickness mm</i>
SG267030	M 3	0,50	19,0	5,0
SG267040	M 4	0,70	19,0	5,0
SG267050	M 5	0,80	19,0	7,0
SG267060	M 6	1,00	19,0	7,0
SG267080	M 8	1,25	22,0	9,0
SG267100	M 10	1,50	27,0	11,0
SG267120	M 12	1,75	36,0	14,0
SG267140	M 14	2,00	36,0	14,0
SG267160	M 16	2,00	41,0	18,0
SG267180	M 18	2,50	41,0	18,0
SG267200	M 20	2,50	41,0	18,0
SG267220	M 22	2,50	50,0	22,0
SG267240	M 24	3,00	50,0	22,0
SG267270	M 27	3,00	60,0	25,0
SG267300	M 30	3,50	60,0	25,0

ZE000001	Boor/Tap gel	s spuitbus	400 ml
	<i>Drill/Tapping gel</i>	<i>aerosol</i>	<i>400 ml</i>
ZE000002	Boor pasta	tube	250 gr
	<i>Drill paste</i>	<i>tube</i>	<i>250 gr</i>
ZE000003	Boor pasta	tube	750 gr
	<i>Drill paste</i>	<i>tube</i>	<i>750 gr</i>

Zeskant-snijmoeren MF DIN 382 HSS, geslepen
Hexagonal solid square bolt die MF DIN 382 HSS, ground



Art. Nr. HSS	Afmeting	Spoed mm	Sleutelwijdte mm	Dikte snijplaat MM
<i>Art. No. HSS</i>	<i>Thread size</i>	<i>Pitch mm</i>	<i>Outside mm</i>	<i>Thickness mm</i>
SH269030	MF 3	0,35	19,0	5,0
SH269040	MF 4	0,35	19,0	5,0
SH269041	MF 4	0,50	19,0	5,0
SH269050	MF 5	0,50	19,0	5,0
SH269051	MF 5	0,75	19,0	7,0
SH269061	MF 6	0,50	19,0	5,0
SH269060	MF 6	0,75	19,0	7,0
SH269070	MF 7	0,75	22,0	9,0
SH269080	MF 8	0,75	22,0	9,0
SH269081	MF 8	1,00	22,0	9,0
SH269102	MF 10	0,75	27,0	11,0
SH269100	MF 10	1,00	27,0	11,0
SH269101	MF 10	1,25	27,0	11,0
SH269121	MF 12	1,00	36,0	10,0
SH269122	MF 12	1,25	36,0	10,0
SH269120	MF 12	1,50	36,0	10,0
SH269142	MF 14	1,00	36,0	10,0
SH269140	MF 14	1,25	36,0	10,0
SH269141	MF 14	1,50	36,0	10,0
SH269161	MF 16	1,00	41,0	14,0
SH269162	MF 16	1,25	41,0	14,0
SH269160	MF 16	1,50	41,0	14,0
SH269181	MF 18	1,00	41,0	14,0
SH269180	MF 18	1,50	41,0	14,0
SH269182	MF 18	2,00	41,0	14,0
SH269201	MF 20	1,00	41,0	14,0
SH269200	MF 20	1,50	41,0	14,0
SH269202	MF 20	2,00	41,0	14,0
SH269221	MF 22	1,00	50,0	16,0
SH269220	MF 22	1,50	50,0	16,0
SH269222	MF 22	2,00	50,0	16,0
SH269242	MF 24	1,00	50,0	16,0
SH269240	MF 24	1,50	50,0	16,0
SH269241	MF 24	2,00	50,0	16,0
SH269261	MF 26	1,50	50,0	16,0
SH269270	MF 27	1,50	60,0	18,0
SH269271	MF 27	2,00	60,0	18,0
SH269301	MF 30	1,50	60,0	18,0
SH269302	MF 30	2,00	60,0	18,0